

COMPREHENSIVE PROTECTION RANGE

ISOLATOR - Provides Total Electrical Isolation

K10I Series



Two Pole Isolator



Three Pole Isolator



Four Pole Isolator

KEVILTON ISOLATOR

- Provides total electrical isolation
- Safely disconnects the power supply from load
- Ensures safety while maintaining and servicing the circuit
- Useful during emergency operations

PRODUCT SPECIFICATIONS

General Data	
Standard Compliance	IEC 60947
Country of Manufacture	People's Republic of China
Warranty	10 Years
Application	
Operation	Used as a total electrical isolating device (Main switch)
Technical Data	
Rated Voltage	230/400V AC
Rated Current	40, 63 & 100A
Rated Frequency	50/60Hz
Electro Mechanical Endurance	10000 cycles
No. of Poles	2P, 3P & 4P
Terminal Space Capacity	25mm ²
Fastening Torque	2 Nm
DIN Rail	Easy mounting on 35mm DIN rail
Mounting Feature in Flush type	Adjustable type DIN rail mounting
Mounting Type	Rail plug in
Connecting Type	Clamping terminal
External Dimensions (L*W*H) mm	1P -78*18*81, 2P -78*36*81, 3P -78*54*81, 4P -78*72*81
Material	
Plastic	Poly Amide (Fire Retardant Grade)
Metal	Phosphor Bronze, Brass, Zinc plated steel